



CAM-5D-21-WDR-LX7

550TVL, Corrosion Proof WDR Pixim Dome Camera, 2.8~11mm Lens, UTP



SPECIFICATION

CAMERA

Style	Dome
Signal System	NTSC, PAL
Image Sensor	Pixim™
Picture Elements	720 H x 540 V
Signal-to-Noise Ratio	> 50 dB
Gain Control	On/Off
Horizontal Resolution	Day: 550TVL Night: 600TVL
Synchronization	Internal / Line Lock
Gamma Correction	0.45 Approx
Scanning System	Progressive
Min. Sensitivity (day)	0.05 Lux - at F1.2
Min. Sensitivity (night)	0.005 Lux - at F1.2
Lens	2.8~11mm Varifocal Lens
Day/Night	YES
Auto Iris	YES
OSD Menu	YES
Wide Dynamic Range (WDR)	YES
3-Way Gimbal	YES
UTP	YES
Vandal-Proof	YES
Corrosion-Proof	YES

ENVIRONMENTAL

Operation Temperature	-4 0°F to +122°F (-4 0°C to +50°C)
Ingress Protection Rating (IEC 60529)	IP67 Weather-Proof
Heater	YES

ELECTRICAL

Video System	Composite Video 1.0Vp-p/75ohm
Signal Connector	RJ45 Jack and BNC-F
Power Supply	12~60VDC, 24/28VAC
Current Draw	500 mA
Power Consumption	6 Watts
PoE / PoE+ Voltage Compatible	YES

PHYSICAL

Dimensions (W x H)	3.7" x 2.7" (94 x 69 mm)
Weight	2.2 lb (998 g)
Housing Material	Delrin™ (polyoxymethylene)
Housing Color	White
Camera Mounting	Wall/ceiling

REGULATORY

Regulatory Type	CE, FCC, UL
-----------------	-------------

Warranty (Effective Jan 1, 2009)

Limited Lifetime

© Aventura Technologies



- 550TVL Corrosion Proof WDR Dome Camera
- 2.8~11mm Varifocal Lens
- Day/Night
- Auto-Iris
- UTP
- 12~60VDC, 24/28VAC

AVAILABLE MODELS

Part number	Description
CAM-5D-21-WDR-LX7	550TVL, Corrosion Proof WDR Pixim Dome Camera, 2.8~11mm Varifocal Lens, Day/Night, OSD, UTP