

CAM-5D-49IR-EB

540 TVL, Vandal Proof Infrared Color Dome Camera



Analog High Resolution Camera Series

Bravo camera series offers superior imaging quality along with a wide selection of superior camera enclosures engineered by Aventura. The Bravo Series cameras have been setting the standards for image perfection. Bravo series cameras excel in challenging low light conditions and are constructed of the finest materials and are ruggedized to withstand the elements. Bravo cameras are available in a variety of lenses and enclosures to meet the requirements of professional CCTV integrators. Most Bravo cameras come with an unprecedented 10-year warranty.

SPECIFICATIONS

SPECIFICATIONS	
CAMERA Series	Bravo
Style System	Eyeball dome
Signal System	NTSC/PAL
Horizontal Resolution (D/N)	540 TVL
Image Sensor	1/3" CCD
Picture Elements	NTSC: 768 (H) x 494(V) PAL: 752 (H) x 582 (V)
Lens	4~9 mm varifocal
FOV Degrees (Horizontal/Vertical)	61.9° (H)/48.4° (V)~29.8° (H)/22.6° (V)
Auto Iris	Yes
Min. Illumination (day)	Color (day) 0.1 lux f1.6
Min. Illumination (night)	B/W (night) 0 lux f1.6
IR Beam Distance	50 ft.
Infrared	Yes
Day/Night (Electronic)	Yes
True Day/Night	
Scanning System	2:1 interlaced
Signal-to-Noise Ratio	≥48 dB (AGC off)
Synchronization	Internal
Gamma Correction	0.45 approx.
Back Light Compensation	Yes
White Balance	Yes
On-Screen Display	
Extra Spot Monitor Output	
PoUTP	
DNR (Digital Noise Reduction)	
WDR (Wide Dynamic Range)	
IR Cut Filter (Mechanical)	
3 Way Axis Gimbal	Yes
Communication	
ACCESSORIES	
Bracket	
Sun Shield	
Remote Control	
Power Pigtail Lead	
ENVIRONMENTAL	
Operation Temperature	1 4°F to 122°F (-1 0°C to 50 °C)
Storage Temperature	-2 2°F to 140°F (-3 0°C to 60 °C)
Operating Humidity	Up to 95%
Ingress Protection Rating (IEC 60529)	IP66
Weatherproof	Yes
Vandal Proof	Yes
ELECTRICAL	100
Video Out	Composite signal 1.0Vp-p/75ohm
	BNC
Signal Connector	12 VDC
Input Voltage Current Draw	400 mA
	4.8 Watts
Power Consumption	4.0 Walls
PHYSICAL	5 10 " a v 2 66" (121 v 02 mm)
Dimensions (W x H)	5.18 " ø x 3.66" (131 x 93 mm)
Weight	1.98 lb (900 g)
Housing Material	Zinc
Housing Color	Champagne metallic
Camera Mounting	Wall/ceiling
REGULATORY	05 500 111
Regulatory Type	CE, FCC, UL
Warranty (Effective Jan 1, 2009)	



- 540 TVL color infrared eyeball camera
 4~9 mm varifocal lens
- Weatherproof (IP66) & Vandal proof
- Electronic day/night & Auto iris 50 feet zero lux illumination 12 VDC

AVAILABLE MODELS

Part number	Description
CAM-5D-491R-EB	540 TVL, vandal proof infrared color eyeball dome camera, 4~9 mm varifocal lens, 50 ft IR

Aventura - World Headquarters

180 Adams Ave. Hauppauge, NY 11788 USA Tel: 631-300-4000 | Fax: 631-434-7000 www.aventuracctv.com

Aventura and the Aventura logo are registered trademarks of Aventura Technologies, Inc.

Specifications subject to change without notice.

©Copyright 2010. All rights reserved

10 Years