



CAM-5Z-10X-WM-O-DN

540TVL 10X Optical Day/Night PTZ, Outdoor Wall/Pendant Mount, 12VDC

SPECIFICATION

CAMERA	
Style	Outdoor PTZ
Signal System	NTSC/PAL
Horizontal Resolution	540 TVL Day / 600 TVL Night
Image Sensor	1/4" CCD
Picture Elements	NTSC: 768 (H) x 494 (V) PAL: 752 (H) x 582 (V)
Zoom	10X Optical, 10X Digital
Lens	3.8~38mm Zoom length
Auto Iris	Yes
Min. Illumination (day)	Color 1 lux at f1.2
Min. Illumination (night)	B/W 0.05 lux at f1.2
Day/Night (Electronics)	Yes
True Day/Night	Yes
Scanning System	2:1 Interlaced
Signal-to-noise Ratio	>50 dB (AGC off)
Synchronization	Internal
Gamma Correction	0.45 approx.
Back Light Compensation	Yes
White Balance	Yes
On-Screen Display	Yes
Communication	RS485
PTZ FEATURE	
Built-In Protocols	Pelco D/P
Image Stabilization	Yes
Alarm	Yes
Pattern Tour	8
Presets	127
Password Protection	Yes
Baud Rate	2400/4800/9600 bps
ACCESSORIES	
Bracket	Yes
ENVIRONMENTAL	
Operation temperature	0 F to 122 F
Storage Temperature	0 F to 122 F
Operating Humidity	95%
Ingress Protection Rating	IP66
Weatherproof	Yes
Vandalproof	Yes
ELECTRICAL	
Video Out	Composite Signal (1 Volt p-p 75 ohm)
Signal Connector	BNC
Input Voltage	12 VDC
Current Draw	750 mA
WARRANTY	
1 Year	

©Aventura Technologies



- Auto tracking, intelligent surveillance with alarm function
- 10X Optical Zoom
- 540 TVL (768 x 494)
- 3.8~38 mm varifocal lens
- 12 VDC

MODELS

Part Number	Description
CAM-5Z-10X-WM-O-DN	540TVL 10X Optical Day/Night PTZ, Outdoor Wall/Pendant Mount, 12VDC