



CAM-6D-21VP-WDR

600 TVL, Vandal Proof Dome Camera, Day/Night, 2.8~12 mm Varifocal Lens, Weatherproof, Dual Voltage



Analog High Resolution Camera Series

Bravo camera series offers superior imaging quality along with a wide selection of superior camera enclosures engineered by Aventura. The Bravo Series cameras have been setting the standards for image perfection. Bravo series cameras excel in challenging low light conditions and are constructed of the finest materials and are ruggedized to withstand the elements. Bravo cameras are available in a variety of lenses and enclosures to meet the requirements of professional CCTV integrators. Most Bravo cameras come with an unprecedented 10-year warranty.

SPECIFICATIONS

CAMERA	
Series	Bravo
Style	Vandal proof dome
Signal System	NTSC/PAL
Horizontal Resolution (D/N)	600 TVL day / 700 TVL night
Image Sensor	1/3" Super HAD II CCD
Picture Elements	NTSC: 768 (H) x 494 (V) PAL: 752 (H) x 582 (V)
Lens	2.8~12 mm varifocal
FOV Degrees (Horizontal/Vertical)	81.2°(H)/65.4°(V)~24.6°(H)/18.5°(V)
Auto Iris	Yes
Min. Illumination (day)	Color (day) 0.12 lux f1.2
Min. Illumination (night)	B/W (night) 0.0002 lux f1.2
Infrared	- - - -
Day/Night (Electronic)	Yes
True Day/Night	Yes
Scanning System	2:1 interlaced
Signal-to-Noise Ratio	≥50 dB (AGC off)
Synchronization	Internal
Gamma Correction	0.45 approx.
Back Light Compensation	Yes
White Balance	Yes
On-Screen Display	Yes
Extra Spot Monitor Output	- - - -
PoUTP	- - - -
DNR (Digital Noise Reduction)	3DNR
WDR (Wide Dynamic Range)	Yes
IR Cut Filter (Mechanical)	Yes
3 Way Axis Gimbal	Yes
Communication	- - - -
ACCESSORIES	
Bracket	- - - -
Sun Shield	- - - -
Power Pigtail Lead	Yes
ENVIRONMENTAL	
Operation Temperature	14°F to 122°F (-10°C to 50 °C)
Storage Temperature	-22°F to 140°F (-3.0°C to 60 °C)
Operating Humidity	Up to 95%
Ingress Protection Rating (IEC 60529)	IP66
Weatherproof	Yes
Vandal Proof	Yes
ELECTRICAL	
Video Out	Composite signal 1.0Vp-p/75ohm
Signal Connector	BNC
Input Voltage	12 VDC/24 VAC
Current Draw	200 mA
Power Consumption	2.5 Watts
PHYSICAL	
Dimensions (W x H)	5.7" ø x 4" (145 x 106 mm)
Weight	2.3 lb (1.04 kg)
Housing Material	Zinc
Housing Color	White
Camera Mounting	Wall/ceiling
REGULATORY	
Regulatory Type	CE, FCC, UL
Warranty (Effective Jan 1, 2009)	
10 Years	

© Aventura



- 600 TVL color dome camera
- 2.8~11 mm varifocal lens
- Weatherproof (IP66) & Vandal proof
- Wide Dynamic Range
- 3DNR
- True day/night & Auto iris
- Dual voltage

AVAILABLE MODELS

Part number	Description
CAM-6D-21VP-WDR	600 TVL, color dome camera, 2.8~12 mm varifocal lens, day/night, vandal proof, weatherproof, dual voltage