

CAM-6X-WDR

600 TVL, Color Box Camera, True Day/Night, Auto Iris, WDR, 3DNR



Analog High Resolution Camera Series

Bravo camera series offers superior imaging quality along with a wide selection of superior camera enclosures engineered by Aventura. The Bravo Series cameras have been setting the standards for image perfection. Bravo series cameras excel in challenging low light conditions and are constructed of the finest materials and are ruggedized to withstand the elements. Bravo cameras are available in a variety of lenses and enclosures to meet the requirements of professional CCTV integrators. Most Bravo cameras come with an unprecedented 10-year warranty.

SPECIFICATIONS

SPECIFICATIONS	
CAMERA	
Series	Bravo
Style	Box camera
Signal System	NTSC/PAL
Horizontal Resolution (D/N)	600 TVL day / 700 TVL night
Image Sensor	1/3" Super HAD II CCD
Picture Elements	NTSC: 768 (H) x 494(V)
-	PAL: 752 (H) x 582 (V)
Lens	Not included (C/CS mount)
FOV Degrees (Horizontal/Vertical)	Varies with lens
Auto Iris	Yes
Min. Illumination (day)	Color (day) 0.12 lux f1.2
Min. Illumination (night)	B/W (night) 0.0002 lux f1.2
IR Beam Distance	
Infrared	
Day/Night (Electronic)	Yes
True Day/Night	Yes
Scanning System	2:1 interlaced
Signal-to-Noise Ratio	≥52 dB (AGC off)
Synchronization	Internal
Gamma Correction	0.45 approx. (OSD)
Back Light Compensation	Yes
White Balance	Yes
On-Screen Display	Yes
Extra Spot Monitor Output	
PoUTP	
DNR (Digital Noise Reduction)	Yes (3DNR)
WDR (Wide Dynamic Range)	Yes
IR Cut Filter (Mechanical)	Yes
3 Way Axis Gimbal	
Communication	
ACCESSORIES	
Bracket	
Sun Shield	
Remote Control	
Power Pigtail Lead	
ENVIRONMENTAL	
Operation Temperature	1 4°F to 122°F (-10°C to 50 °C)
Storage Temperature	-4°F to 140°F (-20°C to 60 °C)
Operating Humidity	Up to 95%
Ingress Protection Rating (IEC 60529)	
Weatherproof	
Vandal Proof	
ELECTRICAL	
Video Out	Composite signal 1.0Vp-p/75ohm
Signal Connector	BNC
Input Voltage	12 VDC/24 VAC
Current Draw	150 mA
Power Consumption	2 Watts
PHYSICAL	
Dimensions (W x H x D)	4.1" x 2.17" x 2.4" (104 x68 x 60 mm)
Weight	1 lb (460 g)
Housing Material	Powder coat
Housing Color	Silver
Camera Mounting	Wall/ceiling
REGULATORY	
*	CE, FCC, UL
Regulatory Type Warranty (Effective Jan 1, 2009)	CL, 100, UL
10 Years	



- 600 TVL color box camera
- Lens not included (C/CS mount)
- 3 Layer DNR
- Wide Dynamic Range
- True day/night Auto iris Dual voltage

AVAILABLE MODELS

Part number	Description
CAM-6X-WDR	600 TVL, 3DNR WDR color box camera, lens not included (C/CS mount), true day/night, auto iris





Aventura - World Headquarters

180 Adams Ave. Hauppauge, NY 11788 USA Tel: 631-300-4000 | Fax: 631-434-7000 www.aventuracctv.com