



CAM-IP-5D-39P

H.264 IP Dome Camera, 4CIF (704x480), 3.5~9 mm
vf Lens, PoE

DATUM
series

Aventura's H.264 IP Dome network cameras utilize a high performance progressive scan ccd sensor and Texas Instruments' advanced digital signal processor. The state-of-the-art DSP technology assures the ultimate in performance in the most challenging environmental conditions. Multiple connection ports support both IP (digital) and composite (analog) video outputs. Advanced H.264 video codec offers high definition resolution and real time recording while conserving network bandwidth. Aventura IP solutions are designed for the enterprise and are ONVIF compliant.

- â€¢ 4CIF Resolution (704x480)
- â€¢ Progressive Scan 540TVL CCD Sensor
- â€¢ True Day/Night/Built in IR Cut Filter
- â€¢ Dual H.264 compression stream
- â€¢ Motion detection/Watermarking
- â€¢ SD Slot/Alarm/Sensor Inputs/outputs
- â€¢ POE (Power Over Ethernet)
- â€¢ ONVIF Compliant
- â€¢ Motion detection Support
- â€¢ VOIP Support
- â€¢ Watermarking
- â€¢ Client and Web Browser Software Included
- â€¢ SDK Available

SPECIFICATIONS

CAMERA	
Image Sensor	Progressive Scan CCD
Image Sensor Size	1/3"
Megapixel Sensor	---
Sensor Size in Megapixel	---
Min. Sensitivity (day)	Color (day) 0.1 lux at f1.2
Min. Sensitivity (night)	B&W (night) 0.004 lux at f1.4
VIDEO	
Day/Night (Electronic)	Yes
Maximum Video Resolution	540 TVL (4CIF)
Frames Per Second NTSC/PAL	30 FPS (704 x 480) / 25 FPS (704 x 576)
Video Output	32Lbps~8Mbps
IR Cut Filter	Yes
LENS	
Focal Length	2.8~12 mm
Varifocal	Yes
Aperture	f1.4
Lens Mount	C/CS
Auto Iris	Yes
COMPRESSION	
Compression Type	H.264 SVC dual stream
AUDIO	
Audio Support	Yes
Two-Way Audio	Yes
Built-In Microphone	---
Built-In Speaker	---
SYSTEM INTEGRATION	
Video Motion Detection	Yes
Audio Detection	Yes
Alarm Inputs/Outputs	1 input / 1 relay output
ePTZ	---
SD Card Local Storage	SD Slot (Up to 32Gb)
Protocol Support	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, PPPoE, SMTP, NTP(SNMP, HTTPS, FTP, SIP, 802.1x, IPv6 optional)
Power Over Ethernet	Class 3
Wireless	---
SECURITY	
Multi-Level Password	Yes
HTTPS Encryption	Yes
IP Address Filtering	Yes
IEEE 802.1X	Yes

© Aventura Technologies



- 4CIF Resolution (704x480)
- Progressive Scan 540TVL CCD Sensor
- True Day/Night, Built in IR Cut Filter
- Dual H.264 compression stream
- Motion detection/Watermarking
- SD Slot/Alarm/Sensor Inputs/outputs
- POE (Power Over Ethernet)
- ONVIF Compliant

AVAILABLE MODELS

Part number	Description
CAM-IP-5D-39P	H.264 IP Dome Camera, 4CIF (704x480), 3.5~9 mm vf Lens, PoE

Aventura - World Headquarters
 180 Adams Ave. Hauppauge, NY 11788 USA
 Tel: 631-300-4000 | Fax: 631-434-7000
www.aventuracctv.com

Aventura and the Aventura logo are registered trademarks of Aventura Technologies, Inc.
 Specifications subject to change without notice. ©Copyright 2011. All rights reserved

CAM-IP-5D-39P

Rev: 051911

ENVIRONMENTAL	
Operation Temperature	14°F to 140°F (-10°C to 60°C)
Storage Temperature	-4°F to 140°F (-20°C to 60°C)
Operating Humidity	Up to 95%
Ingress Protection Rating (IEC 60529)	----
Weatherproof	----
Vandal Proof	----
ACCESSORIES	
Bracket	Optional
Remote Control	----
ELECTRICAL	
Video Out	Composite signal (1Volt p-p 75Ω)
Signal Connector	RJ45/BNC
Input Voltage	12 VDC/PoE
Current Draw	350mA
Power Consumption	5.5 Watts
PHYSICAL	
Dimensions (W/H/D)	5.51" x 4.49" (140mm x 114mm)
Weight	1.3 lb (590 g)
Housing Material	Zinc
Housing Color	Beige
Camera Mounting	Wall/ceiling
REGULATORY	
Regulatory Type	CE, FCC, UL
Warranty (Effective Jan 1, 2009)	
3 Years	