



CWS-2DV-DK Series

Client Remote Workstation

Overview

Monitor and manage DVR servers located in other rooms, buildings, cities, or even countries all on a single screen. Complete control of DVR software, PTZ control, and settings. Playback video and record locally.

SPECIFICATIONS

| SYSTEM | |
|----------------------------------|--|
| Motherboard & Chipset | Intel 865 Chipset |
| CPU | Core 2 Duo, 2.6 GHz E4700 Socket 775 (2 MB Cache) |
| RAM | 1 GB DDR2 667 |
| Storage | 1 TB (Up to 4.5 TB internal SATA) |
| Video Display | 512 MB:ATI Radeon 3650 HD Dual DVI |
| OS | XP Professional |
| Chassis Type | Cube |
| Storage Media | DVD-RW |
| Mouse | Optical PS/2 |
| Keyboard | 106-Key |
| LAN | 10/100/1000 Base T Ethernet |
| Backup Storage | (Optional) DAT- Supports IDE, SCSI, NAS, DDS3/4, RAID |
| HARDWARE | |
| Size | 8.7" x 8.3" x 12.8" |
| Weight | 25 lb |
| Power Supply | Max. 350 W, 90-264 V(47 Hz-65 Hz) |
| Power | 110/220 VAC, 60/50 Hz (non condensing) at 40°C |
| Operating Temperature | 25°F ~ 110°F |
| Power Management | Programmable auto-reboot in case of power loss |
| UPS | External UPS (Optional) |
| MONITORING | |
| Interface | Web Graphical User Interface/Client Software Included |
| Display Rate | Real-Time All Channels Simultaneous (30 FPS/NTSC 25 FPS/PAL) |
| Display Resolution | 4CIF, QCIF, CIF, 2CIF, DCIF |
| Disconnection Detection | Watchdog Function |
| RECORDING | |
| Time Stamp | Image embedded with date/time information |
| Recording Resolution | 4CIF(704x480), DCIF(528x320), 2CIF(704x240), CIF(352x240), QCIF(176x120) |
| Record Rate | Real-Time All Channels Simultaneous (30 FPS/NTSC 25 FPS/PAL) |
| Mode | Normal, Motion Detection, Sensor, Pre-Post Alarm/Scheduled Multi-Channel |
| PLAYBACK | |
| Search Mode | By Channel, Date & Time, Motion Detection, Sensor Events |
| Playback Mode | Play, Pause, Step Play, 1 - 2048 times Fast Forward/Rewind, Scrub |
| Image Adjustment | Brightness, Contrast, Saturation, Hue, Zooming |
| AUTHENTICATION | |
| Authentication | Frame level on DVR and exported on player |
| Encrypted Watermark | AES 128-bit Encryption |
| REMOTE | |
| Monitoring | Full Remote Control PSTN, ISDN, ADSL, LAN and TCP/IP |
| STANDARD | |
| Safety Standards | EN60950, UL1459 |
| APPROVALS | |
| EMC Standards | EN55022 Class-B, EN50082-1 |
| FCC | Part 15 Class-B, VCCI Class-2 |
| Warranty (Effective Jan 1, 2009) | |
| | 1 Year |

© Aventura Technologies



- Monitor and manage DVR's remotely
- Desktop Cube
- 1 TB storage
- 2 DVI outputs
- Up to 4 composite outputs

AVAILABLE MODELS

| Part number | Description |
|----------------|--|
| CWS-2DV-DK | Client Remote Workstation with 1 TB HDD, 2 DVI Outputs |
| CWS-2DV-2CM-DK | Client Remote Workstation with 1 TB HDD, 2 DVI Outputs and 2 Composite Outputs |
| CWS-2DV-4CM-DK | Client Remote Workstation with 1 TB HDD, 2 DVI Outputs and 4 Composite Outputs |

© Aventura Technologies

