



WRS-ANK-58WP

5.8Ghz Analog Video Wireless Transmitter/Receiver

Features:

- Easy to install and operate
- 8 user selectable channels
- Not susceptible to 802.11 b/g wireless data interference
- Delivers high resolution, **Real-Time** video.
- Range from 2000 feet to 4 miles line of sight (depending on optional receiver antenna)
- Rugged All-weather IP-67 protective enclosure
- Includes One Year Limited Warranty
- Perfect for commercial, industrial, scientific, law enforcement and government video security applications

SPECIFICATIONS

Operating Frequency:	5.725 GHz - 5.875 GHz
User Selectable Channels:	8 User Selectable Channels
Radiated Power:	50mV/m @ 3m
Operating Distance Line of Sight:	Up to 2,000 Feet
Range with Optional Rx:	Up to 1 Mile with Optional 14dB Gain Antenna
Antenna:	NTSC or PAL
Video Format:	Tx: 3dB Internal Fixed Directional Patch, Rx: 7dB Internal Removable
Antenna Type:	Directional Patch
Antenna Connector:	SMA Female
Video Connector Format:	BNC Female
Video Impedance & Level:	75 Ohms @ 1 Volt Peak to Peak
Audio Connector Format:	BNC Female
Audio Impedance & Level:	600 Ohms @ 1 Volt Peak to Peak
Temperature Range:	-40F to +170F
Weather Proof:	All-Weather Rated IP-67
Operating Voltage:	9 - 14 Volts DC, Polarity Protected
Power Supply:	Two PS-1250 (Included)
Current Consumption:	Tx - 230mA @ 12 VDC / Rx - 330mA @ 12 VDC
Dimensions:	7.0" x 7.0" x 4.5"
Weight:	0.9kg or 32 oz Each Enclosure
FCC/IC Approved:	Yes
Includes:	All weather Tx & Rx, 12 VDC Power Supplies, Operating Instructions, One Year Limited Warranty
Receiver Sensitivity	-84dBm
Universal Mounting Bracket	BRK-250 Included - wall or pole mount
Warranty (Effective Jan 1, 2009)	
1 Year	

© Aventura Technologies



- 5.8 GHz
- Easy to install and operate.
- Rugged all weather IP67 protective enclosure.
- Eight user selectable channels.
- Up to 2000ft

AVAILABLE MODELS

Part number	Description
WRS-ANK-58WP	5.8Ghz Analog Video, Wireless Transmitter/Receiver Kit. Ruggedized Weatherproof. Up to 2000Ft.